



# 宜特科技股份有限公司



No.:T1091

## Integrated Service Technology Inc.

TEL : (03) 578-2266

RA No: 9503684-E

FAX : (03) 578-2299

Date : 11/07/2006

Email: esd@isti.com.tw

Test Site Address: 1F, No.22, Pu-Ding Rd., Hsin-Chu, Taiwan, R.O.C.

### 可靠度測試報告

### RELIABILITY TEST REPORT

<b>Applicant/Department:</b> 擎力科技股份有限公司	
<b>Address</b> : 台北市南港區園區街 3-2 號 9F-5	
<b>Product</b> : SP6003A	
<b>Testing Item</b> : ESD-HBM	<b>Package/Pin Count:</b> SOP/8
<b>Application Date</b> : 11/06/2006	<b>Date Finished</b> : 11/07/2006
<b>Test Method</b> : MIL-STD-883F Method 3015.7	
<b>Failure Criteria</b> : FOR V CHANGE AT 1μA ±30%	
<b>Test Voltage</b> : 500V~8000V(±) , Step:500V(±)	

Testing Item	
Random ESD-HBM Test.....	P2

**Remark:**

- This report refers only to the specimen submitted to testing, and be invalid as separately used.

<b>Testing Engineer:</b>	Reliability Test Engineer <i>Jay Fang</i>
<b>Report Review:</b>	Reliability Test Engineer <i>Kosa Lin</i>
<b>Laboratory Head:</b>	Manager <i>Kevin Tsui</i>



# 宜特科技股份有限公司

## Integrated Service Technology Inc.

TEL : (03) 578-2266

RA No: 9503684-E

FAX : (03) 578-2299

Date : 11/07/2006

Email: esd@isti.com.tw

Test Site Address: 1F, No.22, Pu-Ding Rd., Hsin-Chu, Taiwan, R.O.C.

### ESD-HBM Testing Report

#### Test Equipment:

KEYTEK ZAPMASTER #1-6380

#### Environmental Condition of Laboratory:

Temperature: 25°C±5°C

Humidity: 55%±10% RH

#### Test Condition:

VSS (+)

VSS (-)

VCC (+)

VCC (-)

VCC – VSS (+)

VCC – VSS (-)

#### Test Result:

MODEL: HBM	ESD SENSITIVITY PASS : <b>+2500V</b>		V CLASS: <u>  2  </u>
PIN COMBINATION	SAMPLE SIZE	PASSED VOLTS	<b>NOTE:</b> FOR MIL-STD CLASS1: 0V-1999V CLASS2: 2000V-3999V CLASS3: 4000V-TO ABOVE
VSS (+)	3	+2500V	
VSS (-)	3	-8000V	
VCC (+)	3	+5500V	
VCC (-)	3	-2500V	
VCC – VSS (+)	3	+8000V	
VCC – VSS (-)	3	-8000V	

ALL:1-4,6,8  
VCC:7

VSS:5

VSS (+) (UNIT:V)									
Test Pin	FAIL VOLTAGE	#1	#2	#3	Test Pin	FAIL VOLTAGE	#1	#2	#3
1		+6500	+6000	+6500	4		+6500	+6000	+5500
2		+6500	+6000	+6000	6		+2500	+3000	+2500
3		+5500	+5500	+4500	8		+7000	+7000	+7000

VSS (-) (UNIT:V)									
Test Pin	FAIL VOLTAGE	#1	#2	#3	Test Pin	FAIL VOLTAGE	#1	#2	#3
1		PASS	PASS	PASS	4		PASS	PASS	PASS
2		PASS	PASS	PASS	6		PASS	PASS	PASS
3		PASS	PASS	PASS	8		PASS	PASS	PASS

VCC (+) (UNIT:V)									
Test Pin	FAIL VOLTAGE	#1	#2	#3	Test Pin	FAIL VOLTAGE	#1	#2	#3
1		+7000	PASS	PASS	4		+8000	+7000	PASS
2		+7500	PASS	+6000	6		PASS	PASS	PASS
3		+7500	+8000	PASS	8		PASS	PASS	PASS

VCC (-) (UNIT:V)									
Test Pin	FAIL VOLTAGE	#1	#2	#3	Test Pin	FAIL VOLTAGE	#1	#2	#3
1		PASS	PASS	PASS	4		PASS	PASS	PASS
2		PASS	PASS	PASS	6		-7000	-7000	-7000
3		PASS	PASS	PASS	8		-2500	-2500	-2500

VCC – VSS (+) (UNIT: V)				
Test Pin	FAIL VOLTAGE	#1	#2	#3
7		PASS	PASS	PASS

VCC – VSS (-) (UNIT: V)				
Test Pin	FAIL VOLTAGE	#1	#2	#3
7		PASS	PASS	PASS