



SPN3006 N-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPN3006 is the N-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology. The SPN3006 has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers. It has been optimized for low gate charge, low $R_{DS(ON)}$ and fast switching speed.



FEATURES

- ◆ 30V/80A, $R_{DS(ON)}=4.7m\Omega@V_{GS}=10V$
- ◆ 30V/80A, $R_{DS(ON)}=7.5m\Omega@V_{GS}=4.5V$
- ◆ Super high density cell design for extremely low $R_{DS(ON)}$
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ TO-252/TO-251 package design


APPLICATIONS

- High Frequency Synchronous Buck Converter
- DC/DC Power System
- Load Switch

PIN CONFIGURATION



PART MARKING



A : Lot Code
B : Date Code

A : Lot Code
B : Date Code



SPN3006

N-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
1	G	Gate
2	D	Drain
3	S	Source

ORDERING INFORMATION

Part Number	Package	Part Marking
SPN3006ST251TGB	TO-251S-3L	SPN3006
SPN3006T252RGB	TO-252-2L	SPN3006

※ SPN3006T252RGB : Tape Reel ; Pb – Free ; Halogen - Free

※ SPN3006ST251TGB: Tube ; Pb – Free; Halogen – Free

ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V _{DSS}	30	V
Gate –Source Voltage	V _{GSS}	±20	V
Continuous Drain Current	I _D	TA=25°C	80
		TA=100°C	57
Pulsed Drain Current	I _{DM}	160	A
Avalanche Current	I _{AS}	48	A
Single Pulse Avalanche Energy	E _{AS}	259	mJ
Power Dissipation	P _D	2	W
Operating Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{STG}	-55/150	°C
Thermal Resistance-Junction to Ambient (t ≤ 10s)	R _{θJA}	62	°C/W



SPN3006

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS

(T_A=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =250μA	30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	1.0		2.5	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =24V, V _{GS} =0V			1	μA
		V _{DS} =24V, V _{GS} =0V, T _J =55°C			5	
On-State Drain Current	I _{D(on)}	V _{DS} ≥5V, V _{GS} =10V			80	A
Drain-Source On-Resistance	R _{DSON}	V _{GS} =10V, I _D =30A		4.7	5.5	mΩ
		V _{GS} =4.5V, I _D =15A		7.5	9	
Forward Transconductance	g _{fs}	V _{DS} =5V, I _D =30A		22		S
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V			1	V
Single Pulse Avalanche Energy	E _{AS}	V _{DD} =25V, L=0.1mH, I _{AS} =24A	60			mJ
Dynamic						
Total Gate Charge	Q _g	V _{DS} =15V, V _{GS} =4.5V I _D =15A		20	18	nC
Gate-Source Charge	Q _{gs}			7.6		
Gate-Drain Charge	Q _{gd}			7.2		
Input Capacitance	C _{iss}	V _{DS} =15V, V _{GS} =0V f=1MHz		2300		pF
Output Capacitance	C _{oss}			265		
Reverse Transfer Capacitance	C _{rss}			210		
Turn-On Time	t _{d(on)}	V _{DD} =15V, I _D =15A, V _{GEN} =10V R _G =3.3Ω		7.8	15	nS
	t _r			15	12	
Turn-Off Time	t _{d(off)}			37	30	
	t _f			10.6	15	



SPN3006 N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS




Fig. 1 Typical Output Characteristics




Fig. 2 Transfer Characteristics




Fig. 3 On-Resistance vs Gate voltage




Fig. 4 Gate Charge Characteristics




Fig. 5 On-Resistance vs Junction Temp









Fig. 6 Vgs vs Junction Temperature



SPN3006 N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS






SPN3006

N-Channel Enhancement Mode MOSFET

TO-252-2L PACKAGE OUTLINE




SYMBOL	MIN	NOM	MAX
A	2.20	2.30	2.40
A1	0.00	--	0.15
A2	0.90	1.01	1.10
b	0.72	-	0.85
b2	0.72	--	0.90
b3	5.13	5.33	5.46
c	0.47	--	0.60
c2	0.47	--	0.60
D	6.00	6.10	6.20
D1	5.25	--	--
E	6.40	6.60	6.80
E1	4.70	--	--
e	2.3REF		
H	9.80	10.10	10.40
L	1.40	1.60	1.80
L1	2.90REF		
L2	0.508BSC		
L3	0.90	--	1.25
L4	0.60	0.80	1.00
L5	0.15	--	0.75
L6	1.80REF		
θ	0°	3°	8°
θ_1	5°	7°	9°
θ_2	5°	7°	9°



SPN3006

N-Channel Enhancement Mode MOSFET

TO-251S-3L PACKAGE OUTLINE



SYMBOL	MIN	NOM	MAX
A	2.20	2.30	2.40
A2	0.86	1.01	1.16
b	0.66	-	0.86
b2	0.66	--	0.96
b3	5.10	5.28	5.46
c	0.46	--	0.60
c2	0.47	--	0.60
D	6.00	6.10	6.20
D1	5.35REF		
E	6.40	6.60	6.80
E1	4.83REF		
e	2.3REF		
H	9.80	10.40	11.00
L1	3.50REF		
L2	0.508BSC		
L3	0.90	--	1.25
L5	0.15	--	0.75
L6	1.80REF		
θ 1	5°	7°	9°
θ 2	5°	7°	9°



SPN3006

N-Channel Enhancement Mode MOSFET

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

© The SYNC Power logo is a registered trademark of SYNC Power Corporation

© 2018 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan 115

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

© <http://www.syncpower.com>