



# SPN80T06

## N-Channel Enhancement Mode MOSFET

### DESCRIPTION

The SPN80T06 is the N-Channel logic enhancement mode power field effect transistor which is produced using super high cell density DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suitable for synchronous rectifier application, Motor control power management and other Power Tool circuits. It has been optimized for low gate charge, low  $R_{DS(ON)}$  and fast switching speed.

### FEATURES

- ◆ 60V/20A,  $R_{DS(ON)}=9m\Omega@V_{GS}=10V$   
60V/20A,  $R_{DS(ON)}=13m\Omega@V_{GS}=4.5V$
- ◆ Super high density cell design for extremely low  $R_{DS(ON)}$
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ TO-220-3L/PPAK5x6 package design




### APPLICATIONS

- DC/DC Converter
- Load Switch
- SMPS Secondary Side Synchronous Rectifier
- Motor Control
- Power Tool


### PIN CONFIGURATION

TO-220-3L


PPAK5x6



### PART MARKING



AAAAA: Wafer lot no  
BBBBBB : date code



A : Lot Code  
B : Date Code  
(YY / MM / DD)



# SPN80T06

## N-Channel Enhancement Mode MOSFET

### TO-220-3L PIN DESCRIPTION

Pin	Symbol	Description
1	G	Gate
2	D	Drain
3	S	Source

### PPAK5x6 PIN DESCRIPTION

Pin	Symbol	Description
1	S	Source
2	S	Source
3	S	Source
4	G	Gate
5	D	Drain
6	D	Drain
7	D	Drain
8	D	Drain

### ORDERING INFORMATION

Part Number	Package	Part Marking
SPN80T06T220TGB	TO-220-3L	SPN80T06
SPN80T06DN8RGB	PDFN5x6-8L	SPN80T06

※ SPN80T06T220TGB : Tube ; Pb – Free ; Halogen - Free

※ SPN80T06DN8RGB : Tape&Reel ; Pb – Free ; Halogen - Free



# SPN80T06

## N-Channel Enhancement Mode MOSFET

### ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit	
Drain-Source Voltage	VDSS	60	V	
Gate-Source Voltage	VGSS	±20	V	
Continuous Drain Current(TO-220-3L)	ID	TA=25°C	80	A
		TA=70°C	55	
Continuous Drain Current(PPAK5x6)	ID	TA=25°C	62	A
		TA=70°C	39	
Pulsed Drain Current (TO-220-3L)	IDM	320	A	
Pulsed Drain Current (PPAK5x6)	IDM	270	A	
Power Dissipation (TA=25°C)	PD	TO-220-3L	268	W
		PPAK5x6	62.5	
Avalanche Energy with Single Pulse (Tj=25°C, L = 1.0mH , I=18A)	EAS	162	mJ	
Operating Junction Temperature	TJ	-55/150	°C	
Storage Temperature Range	TSTG	-55/150	°C	
Thermal Resistance-Junction to Ambient	RθJA	65	°C/W	



# SPN80T06

## N-Channel Enhancement Mode MOSFET

### ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	60			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1.0	1.8	2.4	V
Gate Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 20V$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=48V, V_{GS}=0V$ $T_J=25^\circ C$			1	uA
		$V_{DS}=48V, V_{GS}=0V$ $T_J=100^\circ C$			100	
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=20A$		7.3	9	mΩ
		$V_{GS}=4.5V, I_D=20A$		10	13	
Gate Resistance	$R_G$	$V_{GS}=0V, V_{DS}$ open, $f=1MHz$		1.5		Ω
Diode Forward Voltage	$V_{SD}$	$I_S=20A, V_{GS}=0V$		0.9	1.2	V
<b>Dynamic</b>						
Total Gate Charge (10V)	$Q_g$	$V_{DS}=30V, V_{GS}=10V$ $I_D=20A$		24		nC
Total Gate Charge (4.5V)	$Q_g$			12		
Gate-Source Charge	$Q_{gs}$			5.0		
Gate-Drain Charge	$Q_{gd}$			3.0		
Input Capacitance	$C_{iss}$	$V_{DS}=30V, V_{GS}=0V$ $f=1MHz$		1620		pF
Output Capacitance	$C_{oss}$			415		
Reverse Transfer Capacitance	$C_{rss}$			3		
Turn-On Time	$t_{d(on)}$	$V_{DD}=30V, I_D=20A$ $V_{GEN}=10V, R_G=10\Omega$		9		nS
	$t_r$			4		
Turn-Off Time	$t_{d(off)}$			29		
	$t_f$			4		



# SPN80T06 N-Channel Enhancement Mode MOSFET

## TYPICAL CHARACTERISTICS

Fig 1. Typical Output Characteristics




Figure 2. On-Resistance vs. Gate-Source Voltage




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. Normalized On-Resistance vs. Junction Temperature




Figure 5. Typical Transfer Characteristics





Figure 6. Typical Source-Drain Diode Forward Voltage





# SPN80T06

# N-Channel Enhancement Mode MOSFET

## TYPICAL CHARACTERISTICS

Figure 7. Typical Gate-Charge vs. Gate-to-Source Voltage




Figure 8. Typical Capacitance vs. Drain-to-Source Voltage




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature





Figure 11. Normalized Maximum Transient Thermal Impedance, Junction-to-Case






# SPN80T06

## N-Channel Enhancement Mode MOSFET

### TO-220-3L PACKAGE OUTLINE




SYMBOL	MIN	NOM	MAX
A	4.40	4.50	4.60
A1	1.27	1.30	1.33
A2	2.30	2.40	2.50
b	0.70	—	0.90
b1	1.42	—	1.57
c	0.45	0.50	0.60
D	15.30	15.70	16.10
D1	9.10	9.20	9.30
D2	13.10	—	13.70
E	9.70	9.90	10.20
E1	7.80	8.00	8.20
e	2.54BSC		
e1	5.08BSC		
H1	6.30	6.50	6.70
L	12.78	13.08	13.38
L1	—	—	3.50
L2	4.60REF		
øP	3.55	3.60	3.65
Q	2.73	—	2.87
ø1	1°	3°	5°



# SPN80T06

## N-Channel Enhancement Mode MOSFET

### PPAK5X6 PACKAGE OUTLINE



SYMBOL	MILLIMETERS		
	MIN	NOM	MAX
A	0.8	0.95	1.1
A1	0.00	0.03	0.05
b	0.33	0.41	0.51
c	0.254 REF		
D	4.80	4.95	5.10
F	1.40 REF		
E	5.70	5.80	5.90
e	1.27 BSC		
H	5.90	6.05	6.20
L1	0.06	0.13	0.20
G	0.60 REF		
J	0.95 BSC		
K	4.00 REF		
L	---	----	0.20
P	1.00 REF		
E1	3.40REF		
E2	0.95 REF		
$\theta$	6°	10°	14°
R	0.25REF		





# SPN80T06

## N-Channel Enhancement Mode MOSFET

---

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

© The SYNC Power logo is a registered trademark of SYNC Power Corporation

© 2017 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan 115

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

© <http://www.syncpower.com>