



SPN80T06

N-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPN80T06 is the N-Channel logic enhancement mode power field effect transistor which is produced using super high cell density DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suitable for synchronous rectifier application, Motor control power management and other Power Tool circuits. It has been optimized for low gate charge, low $R_{DS(ON)}$ and fast switching speed.

FEATURES

- ◆ 60V/80A, $R_{DS(ON)}=9m\Omega@V_{GS}=10V$
60V/80A, $R_{DS(ON)}=13m\Omega@V_{GS}=4.5V$
- ◆ Super high density cell design for extremely low $R_{DS(ON)}$
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ TO-220-3L/PPAK5x6-8L package design




APPLICATIONS

- DC/DC Converter
- Load Switch
- SMPS Secondary Side Synchronous Rectifier
- Motor Control
- Power Tool


PIN CONFIGURATION

TO-220-3L


PPAK5x6



PART MARKING



AAAAA: Wafer lot no
BBBBBB: date code



A : Lot Code
B : Date Code
(YY/MM/DD)



SPN80T06

N-Channel Enhancement Mode MOSFET

TO-220-3L PIN DESCRIPTION

Pin	Symbol	Description
1	G	Gate
2	D	Drain
3	S	Source

PPAK5x6-8L PIN DESCRIPTION

Pin	Symbol	Description
1	S	Source
2	S	Source
3	S	Source
4	G	Gate
5	D	Drain
6	D	Drain
7	D	Drain
8	D	Drain

ORDERING INFORMATION

Part Number	Package	Part Marking
SPN80T06T220TGB	TO-220-3L	SPN80T06
SPN80T06DN8RGB	PDFN5x6-8L	SPN80T06

※ SPN80T06T220TGB : Tube ; Pb – Free ; Halogen - Free

※ SPN80T06DN8RGB : Tape&Reel ; Pb – Free ; Halogen - Free



SPN80T06

N-Channel Enhancement Mode MOSFET

ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit	
Drain-Source Voltage	VDSS	60	V	
Gate-Source Voltage	VGSS	±20	V	
Continuous Drain Current(TO-220-3L)	ID	TA=25°C	80	A
		TA=70°C	55	
Continuous Drain Current(PPAK5x6)	ID	TA=25°C	62	A
		TA=70°C	39	
Pulsed Drain Current	IDM	270	A	
Power Dissipation (TA=25°C)	PD	TO-220-3L	104	W
		PPAK5x6	83	
Avalanche Energy with Single Pulse (Tj=25°C, L = 1.0mH, I=18A)	EAS	162	mJ	
Operating Junction Temperature	TJ	-55/150	°C	
Storage Temperature Range	TSTG	-55/150	°C	
Thermal Resistance-Junction to Case (TO-220)	RθJC	1.2	°C/W	
Thermal Resistance-Junction to Case (PPAK5x6)	RθJC	1.5	°C/W	

Note :

The maximum current rating is package limited at 120A for TO-220-3L
The maximum current rating is package limited at 80A for PPAK5x6-8L



SPN80T06

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	60			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1.0	1.8	2.4	V
Gate Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=48V, V_{GS}=0V$ $T_J=25^\circ C$			1	uA
		$V_{DS}=48V, V_{GS}=0V$ $T_J=100^\circ C$			100	
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=20A$		7.3	9	mΩ
		$V_{GS}=4.5V, I_D=20A$		10	13	
Gate Resistance	R_G	$V_{GS}=0V, V_{DS}$ open, $f=1MHz$		1.5		Ω
Diode Forward Voltage	V_{SD}	$I_S=20A, V_{GS}=0V$		0.9	1.2	V
Dynamic						
Total Gate Charge (10V)	Q_g	$V_{DS}=30V, V_{GS}=10V$ $I_D=20A$		24		nC
Total Gate Charge (4.5V)	Q_g			12		
Gate-Source Charge	Q_{gs}			5.0		
Gate-Drain Charge	Q_{gd}			3.0		
Input Capacitance	C_{iss}	$V_{DS}=30V, V_{GS}=0V$ $f=1MHz$		1620		pF
Output Capacitance	C_{oss}			415		
Reverse Transfer Capacitance	C_{rss}			3		
Turn-On Time	$t_{d(on)}$	$V_{DD}=30V, I_D=20A$ $V_{GEN}=10V, R_G=10\Omega$		9		nS
	t_r			4		
Turn-Off Time	$t_{d(off)}$			29		
	t_f			4		



SPN80T06 N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS

Fig 1. Typical Output Characteristics




Figure 2. On-Resistance vs. Gate-Source Voltage




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. Normalized On-Resistance vs. Junction Temperature




Figure 5. Typical Transfer Characteristics





Figure 6. Typical Source-Drain Diode Forward Voltage





SPN80T06

N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS

Figure 7. Typical Gate-Charge vs. Gate-to-Source Voltage




Figure 8. Typical Capacitance vs. Drain-to-Source Voltage




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature





Figure 11. Normalized Maximum Transient Thermal Impedance, Junction-to-Case






SPN80T06

N-Channel Enhancement Mode MOSFET

TO-220-3L PACKAGE OUTLINE




SYMBOL	MIN	NOM	MAX
A	4.50	4.70	4.83
A1	2.34	2.54	2.74
A2	0.7REF		
A3	2.56	2.76	2.93
b	0.70	--	0.90
b1	1.18	--	1.40
b2	--	--	1.47
c	0.45	0.50	0.60
D	15.67	15.87	16.07
D1	15.55	15.75	15.95
D2	9.60	9.80	10.00
E	9.96	10.16	10.36
e	2.54BSC		
H1	6.48	6.68	6.88
L	12.68	12.98	13.28
L1	-	-	3.50
L2	6.50REF		
φ P	3.08	3.18	3.28
Q	3.20	-	3.40
θ 1	1°	3°	5°



SPN80T06

N-Channel Enhancement Mode MOSFET

PPAK5X6 PACKAGE OUTLINE



SYMBOL	MILLIMETERS		
	MIN	NOM	MAX
A	0.8	0.95	1.1
A1	0.00	0.03	0.05
b	0.33	0.41	0.51
c	0.254 REF		
D	4.80	4.95	5.10
F	1.40 REF		
E	5.70	5.80	5.90
e	1.27 BSC		
H	5.90	6.05	6.20
L1	0.06	0.13	0.20
G	0.60 REF		
J	0.95 BSC		
K	4.00 REF		
L	---	----	0.20
P	1.00 REF		
E1	3.40REF		
E2	0.95 REF		
θ	6°	10°	14°
R	0.25REF		



SPN80T06

N-Channel Enhancement Mode MOSFET

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

© The SYNC Power logo is a registered trademark of SYNC Power Corporation

© 2017 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan 115

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

© <http://www.syncpower.com>