



SPN9912

N-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPN9912 is the N-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for most of synchronous buck converter applications.

APPLICATIONS


- DC/DC Converter
- Load Switch
- Synchronous Buck Converter

FEATURES


- ◆ 60V/20A, $R_{DS(ON)}=16m\Omega$ @ $V_{GS}=10V$
- ◆ 60V/20A, $R_{DS(ON)}=19m\Omega$ @ $V_{GS}=4.5V$
- ◆ Super high density cell design for extremely low $R_{DS(ON)}$
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ TO-252-2L/TO-251-3L package design

PIN CONFIGURATION



TO-252



TO-251



PART MARKING





SPN9912

N-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
1	G	Gate
2	D	Drain
3	S	Source

ORDERING INFORMATION

Part Number	Package	Part Marking
SPN9912T252RGB	TO-252-2L	SPN9912
SPN9912T251TGB	TO-251-3L	SPN9912

※ SPN9912T252RGB: Tape Reel ; Pb – Free; Halogen – Free

※ SPN9912T251TGB: Tube ; Pb – Free; Halogen – Free

ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V _{DSS}	60	V
Gate –Source Voltage	V _{GSS}	±20	V
Continuous Drain Current(T _J =150°C)	T _A =25°C	46	A
	T _A =100°C	33	
Pulsed Drain Current	I _{DM}	203	A
Avalanche Current	I _{AS}	27	A
Power Dissipation	P _D	71	W
Avalanche Energy with Single Pulse (T _j =25°C , L= 0.1mH , I _{AS} = 38A)	E _{AS}	36	mJ
Operating Junction Temperature	T _J	-55/150	°C
Storage Temperature Range	T _{STG}	-55/150	°C
Thermal Resistance-Junction to Case	R _{θJC}	2.1	°C/W



SPN9912

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)







Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, ID=250uA	60			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , ID=250uA	1.0		3.0	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =48V, V _{GS} =0V			1	uA
		V _{DS} =48V, V _{GS} =0V T _J =150°C			100	
Drain-Source On-Resistance	R _{DSS(on)}	V _{GS} =10V, ID=20A		13	16	mΩ
		V _{GS} =4.5V, ID=20A		16	19	
Gate Resistance	R _G			1.3		Ω
Forward Transconductance	g _{fs}	V _{DS} =15V, ID=20A		15		S
Diode Forward Voltage	V _{SD}	I _S =40A, V _{GS} =0V			1.2	V
Dynamic						
Total Gate Charge	Q _{g(10V)}	V _{DS} =48V, V _{GS} =10V ID=40A		29		nC
Gate-Source Charge	Q _{gs}			4		
Gate-Drain Charge	Q _{gd}			8		
Total Gate Charge	Q _{g(4.5V)}	V _{DS} =48V, V _{GS} =4.5V ID=40A		15		
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V f=1MHz		1400		pF
Output Capacitance	C _{oss}			137		
Reverse Transfer Capacitance	C _{rss}			95		
Turn-On Time	t _{d(on)}	V _{DD} =48V, ID=40A, V _{GEN} =10V, R _G =2.5Ω		8.4		nS
	t _r			12.4		
Turn-Off Time	t _{d(off)}			26		
	t _f			4.4		



SPN9912

N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS







SPN9912

N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS





SPN9912

N-Channel Enhancement Mode MOSFET

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

© The SYNC Power logo is a registered trademark of SYNC Power Corporation

© 2020 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1 Park Street

NanKang District (NKSP), Taipei, Taiwan 115

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

© <http://www.syncpower.com>